







81.50 BOSKA



	NORM NORMA STANDARD	NORM VORGESCHRIEBENER WERTE VALORI PRESCRITTI DALLA NORMA NORM REQUIRED VALUES	EUVAL® WERTE VALORI EUVAL® EUVAL® VALUES
 BIEGEZUGFESTIGKEIT RESISTENZA ALLA FLESSIONE FLEXION RESISTANCE	DIN EN 13748-1	≥ 5 N/mm ²	10,6 N/mm ²
 SCHLEIFVERSCHLEIß RESISTENZA ALL'ABRASIONE ABRASION RESISTANCE	DIN EN 13748-1	< 30 cm ³ / 50 cm ²	13,8 cm ³ / 50 cm ²
 WASSERAUFNAHME ASSORBIMENTO D'ACQUA WATER ABSORPTION	DIN EN 13748-1	< 8 %	3,6 %
 RUTSCHEMMENDE KLASSE BRG 181 CLASSE DI RESISTENZA ALLO SCIVOLO CLASSIFICATION OF ANTI SLIP PROPERTIES	DIN 51130		R9 R10 R11
 BRANDVERHALTEN RESISTENZA AL FUOCO FIRE RESISTANCE	DIN EN 13748-1	A1 _{fl} NICHT BRENNBAR NON INFIAMMABILE NOT FLAMMABLE	A1 _{fl} NICHT BRENNBAR NON INFIAMMABILE NOT FLAMMABLE
 GEWICHTE PESO SPECIFICO APPARENTE SPECIFIC GRAVITY			2.600 kg/m ³

Für die Original Zertifikate stellen Sie sich mit Euragglo s.r.l. in Verbindung.

Per i certificati originali, contattare Euragglo s.r.l.

For the original certificates, please contact Euragglo s.r.l.

